

```
<?xml version="1.0" encoding="utf-8"?>

<xsl:stylesheet version="1.0"
    xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
    xmlns:zs="http://www.loc.gov/zing/srw/"
    xmlns:marc="http://www.loc.gov/MARC21/slim">
<xsl:output method="xml" indent="yes"/>
<xsl:template match="/">
    <ResultSet>
        <RecordCount><xsl:value-of select="//zs:numberOfRecords" /></RecordCount>
        <xsl:call-template name="facet"/>
        <xsl:call-template name="doc"/>
    </ResultSet>
</xsl:template>

<xsl:template name="doc">
    <xsl:for-each select="//zs:records/zs:record">
        <record>
            <id><xsl:value-of select=".//marc:controlfield[@tag=001]" /></id>

            <xsl:if test=".//marc:datafield[@tag='245']/marc:subfield[@code='h']">
                <format><xsl:value-of select=".//marc:datafield[@tag='245']/marc:subfield[@code='h']" /></format>
            </xsl:if>

            <language>
                <xsl:value-of select="substring(.//marc:controlfield[@tag=008], 36, 3)" />
            </language>

            <isbn>
                <xsl:value-of select=".//marc:datafield[@tag='020']/marc:subfield[@code='a']" />
            </isbn>

            <issn>
                <xsl:value-of select=".//marc:datafield[@tag='022']/marc:subfield[@code='a']" />
            </issn>

            <xsl:choose>
                <xsl:when test=".//marc:datafield[@tag='090']">
                    <callnumber>
                        <xsl:value-of select=".//marc:datafield[@tag='090']/marc:subfield[@code='a']" />
                        <xsl:value-of select=".//marc:datafield[@tag='090']/marc:subfield[@code='b']" />
                    </callnumber>
                </xsl:when>
                <xsl:otherwise>
                    <xsl:if test=".//marc:datafield[@tag='050']">
                        <callnumber>
                            <xsl:value-of select=".//marc:datafield[@tag='050']/marc:subfield[@code='a']" />
                            <xsl:value-of select=".//marc:datafield[@tag='050']/marc:subfield[@code='b']" />
                        </callnumber>
                    </xsl:if>
                </xsl:otherwise>
            </xsl:choose>

            <xsl:if test=".//marc:datafield[@tag='100']">
                <author><xsl:value-of select=".//marc:datafield[@tag='100']/marc:subfield[@code='a']" /></author>
            </xsl:if>
        </record>
    </xsl:for-each>
</xsl:template>
```

```
</xsl:if>

<title>
  <xsl:value-of select=".//marc:datafield[@tag='245']/marc:subfield[@code='a']"/>
  <xsl:if test=".//marc:datafield[@tag='245']/marc:subfield[@code='b']">
    <xsl:text> </xsl:text>
    <xsl:value-of select=".//marc:datafield[@tag='245']/marc:subfield[@code='b']"/>
  </xsl:if>
</title>

<xsl:if test=".//datafield[@tag='260']">
  <publisher><xsl:value-of select=".//datafield[@tag='260']/subfield[@code='b']"/>
  </publisher>
  <publishDate><xsl:value-of select=".//datafield[@tag='260']/subfield[@code='c']"/>
  </publishDate>
</xsl:if>

<xsl:if test=".//datafield[@tag='440']">
  <series><xsl:value-of select=".//marc:datafield[@tag='440']/marc:subfield[@code='a']"
  /></series>
</xsl:if>

<xsl:for-each select=".//marc:datafield[@tag='856']">
  <url><xsl:value-of select=".//marc:subfield[@code='u']"/></url>
</xsl:for-each>

<xsl:call-template name="holding"/>

</record>
</xsl:for-each>
</xsl:template>

<xsl:template name="facet">
<Facets>
  <xsl:for-each select="//lst[@name='facet_fields']/lst">
    <Cluster>
      <xsl:attribute name="name"><xsl:value-of select="@name"/></xsl:attribute>
      <xsl:for-each select=".//int">
        <xsl:variable name="elem" select=".//@name"/>
        <item>
          <xsl:attribute name="count"><xsl:value-of select=".//int/@name"/></xsl:attribute>
          <xsl:value-of select="@name"/>
        </item>
      </xsl:for-each>
    </Cluster>
  </xsl:for-each>
</Facets>
</xsl:template>

<xsl:template name="holding">
<xsl:for-each select=".//marc:datafield[@tag='952']">
<holdings>
  <withdrawn><xsl:value-of select=".//marc:subfield[@code='0']"/></withdrawn>
  <itemlost><xsl:value-of select=".//marc:subfield[@code='1']"/></itemlost>
  <cn_source><xsl:value-of select=".//marc:subfield[@code='2']"/></cn_source>
  <materials><xsl:value-of select=".//marc:subfield[@code='3']"/></materials>
  <damaged><xsl:value-of select=".//marc:subfield[@code='4']"/></damaged>
```

```
<restricted><xsl:value-of select=".//marc:subfield[@code='5']"/></restricted>
<cn_sort><xsl:value-of select=".//marc:subfield[@code='6']"/></cn_sort>
<notforloan><xsl:value-of select=".//marc:subfield[@code='7']"/></notforloan>
<ccode><xsl:value-of select=".//marc:subfield[@code='8']"/></ccode>
<itemnumber><xsl:value-of select=".//marc:subfield[@code='9']"/></itemnumber>
<homebranch><xsl:value-of select=".//marc:subfield[@code='a']"/></homebranch>
<holdingbranch><xsl:value-of select=".//marc:subfield[@code='b']"/></holdingbranch>
<location><xsl:value-of select=".//marc:subfield[@code='c']"/></location>
<dateaccessioned><xsl:value-of select=".//marc:subfield[@code='d']"/></dateaccessioned>
<booksellerid><xsl:value-of select=".//marc:subfield[@code='e']"/></booksellerid>
<coded_location_qualifier><xsl:value-of select=".//marc:subfield[@code='f']"/>
</coded_location_qualifier>
<price><xsl:value-of select=".//marc:subfield[@code='g']"/></price>
<renewals><xsl:value-of select=".//marc:subfield[@code='j']"/></renewals>
<stack><xsl:value-of select=".//marc:subfield[@code='j']"/></stack>
<issues><xsl:value-of select=".//marc:subfield[@code='l']"/></issues>
<renewals><xsl:value-of select=".//marc:subfield[@code='m']"/></renewals>
<reserves><xsl:value-of select=".//marc:subfield[@code='n']"/></reserves>
<itemcallnumber><xsl:value-of select=".//marc:subfield[@code='o']"/></itemcallnumber>
<barcode><xsl:value-of select=".//marc:subfield[@code='p']"/></barcode>
<onloan><xsl:value-of select=".//marc:subfield[@code='q']"/></onloan>
<datelastseen><xsl:value-of select=".//marc:subfield[@code='r']"/></datelastseen>
<datelastborrowed><xsl:value-of select=".//marc:subfield[@code='s']"/></datelastborrowed>
<copynumber><xsl:value-of select=".//marc:subfield[@code='t']"/></copynumber>
<uri><xsl:value-of select=".//marc:subfield[@code='u']"/></uri>
<replacementprice><xsl:value-of select=".//marc:subfield[@code='v']"/></replacementprice>
<replacementpricedate><xsl:value-of select=".//marc:subfield[@code='w']"/>
</replacementpricedate>
<paidfor><xsl:value-of select=".//marc:subfield[@code='x']"/></paidfor>
<itype><xsl:value-of select=".//marc:subfield[@code='y']"/></itype>
<itemnotes><xsl:value-of select=".//marc:subfield[@code='z']"/></itemnotes>
</holdings>
</xsl:for-each>
</xsl:template>
</xsl:stylesheet>
```