

```
# Define Path
Alias /vufind c:/vufind/web
<Directory c:/vufind/web/>
    Order allow,deny
    allow from all
    AllowOverride All

# Uncomment the following lines, if you wish to use the Shibboleth authentication
# AuthType shibboleth
# require shibboleth

# Friendly URLs
#
# You may need to adjust the RewriteBase to match your VuFind path.
# You can remove the line if your vufind instance will be located at the web
# server root.
#
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteBase /vufind
    # Note: The following RewriteRule directives include the [B] flag to escape
    # backreferences. This prevents encoding problems caused by special characters
    # like & if they show up in ids. Note that the flag doesn't work in some
    # versions of Apache prior to 2.2.12; if you run into trouble, try upgrading.
    RewriteRule ^(\MyResearch)/([^/]+)/(.+)$ index.php?module=$1&action=$2&id=$3
    [B,L,QSA]
    RewriteRule ^(\Record)/([^/]+)/(.+)$ index.php?module=$1&id=$2&action=$3
    [B,L,QSA]
    RewriteRule ^(\Record)/(.+)$ index.php?module=$1&id=$2
    [B,L,QSA]
    RewriteRule ^([^/]+)/(.+)$ index.php?module=$1&action=$2
    [B,L,QSA]
</IfModule>

# Disable Magic Quotes
php_value magic_quotes_gpc false

# Session Settings
php_value session.use_cookies 1
php_value session.use_only_cookies 1
# important: we want to serialize objects
php_value session.auto_start 0
#php_value session.cookie_secure 1
# we should check session lifetime in "read" methods
# since PHP cookies do not "refresh" them during activity
# hence we leave them alive until browser closes
php_value session.cookie_lifetime 0
php_value session.gc_maxlifetime 6000

# Dynamic CSS
AddType application/x-httpd-php .css

## Uncomment these lines if you wish to show all errors on the screen.
#php_value display_errors 1
#php_value error_reporting 2047
</Directory>
```

```
# Process Login for Administration Module (note use of regular expression in
# Location to ensure matches in case-insensitive environments like Windows).
<Location ~ "[Vv][Uu][Ff][Ii][Nn][Dd]/[Aa][Dd][Mm][Ii][Nn]/.+">
  AuthUserFile c:/vufind/web/services/Admin/.htpasswd
  AuthName "VuFind Administration"
  AuthType Basic
  require valid-user
</Location>
```